IPC ASSOCIATION ELECTRONIC	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved international and Pan-American copyright conventions.			nder both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with local level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					eous Materia	ials and Mfg Information					
upplier	r Information															
Company name* Company unique				ique ID	ue ID U:			Unique ID Authority					Response Date*			
nsemi												2023-06-08				
ontact N	lame	Title - Contact			F	Phone - Contact*				Email - Contact*						
Product-H	Env-Stewards	Product Enviro Compliance]	NA				Product-Env-Stewards@onsemi.com						
Authorized Representative* Title				Fitle - Representative			Phone - Representative*				Email - Representative*					
Product-Env-Stewards Product Enviro Con				iro Compliance	Compliance			NA				Product-Env-Stewards@onsemi.com				
	Requester Item Number	Mfr Iten	n Number	Mfr Item Name			Effective Date	Versio	on	Manufacturing Site			Weight*	UOM	Unit Type	
	FAN4800.		0AUN	AUN PWM PFC Combo			2023-06-08 TAD			1077.722	mg	Each				
lanufa	cturing Process Inform		Terminal Base	Alloy	-STD-020 MS	I Pating	Peak Proc	ess Rody	/ Temperat	ıre May T	ime at Peak	Temperat	ure Numbe	r of Reflow Cyo	plas	
	8		CU Alloy NA			L Rating	0	Process Body Temperature Max			1				Lies	
omments	. ,		oc mily	1	11.5				10	150		Secon	us jo			
iiiiiiiiii	,															
or more i	information regarding materia	al composition	nlease refer to	n nage 3												

RoHS Material Composition Declaration			Declaration Type *	Detail	ed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		ium (Cr6+), Polybrominated Biphenyls (PB)	erial for Cadmium and quantity limit of 0.1% b B), Polybrominated Diphenyl Ethers (PBDE), a		
cadmium, hexavalentchromium, polybromin contains a RoHS restricted substance inexce encompass all such components. Supplier cet as of the date that Supplier completes this Company acknowledges that Supplier may hindependently verified information provided certification in this paragraph. If the Compan	nated biphenyls and/or polybrominated diphess of an applicable quantity limit, please indriffes that it gathered the information it provom. Supplier acknowledges that Company wave relied on informationprovided by others of the supplier agrees that, at a minimusy and the Supplier enter into a written agree yesource of the Supplier's liability and the C	enyl ethers (each a "RoHS restricted substan licate below which, if any, RoHS exemption vides in this form using appropriate methods vill rely on this certification in determining the s in completing this form, and that Supplier um, itssuppliers have provided certifications ement with respect to the identified part, the tompany's remedies for issues that arise rega	s of the European Union member states) of the ce") in excess of the applicable quantity limit is you believe may apply. If the part is an assemb to ensure its accuracy and that such informatio e compliance of its products with European Ur may not have independently verified such infor regarding their contributions to the part, and the erms and conditions of that agreement, including information the Supplier provides in this	dentified above. If a ally with lower level in is true and correct tion member state la mation. However, in ose certifications are ag any warranty righ	homogeneous material within the part components, the declaration shall to the best of its knowledge and belief, was that implement the RoHS Directive. In situations where Supplier has not the at least as comprehensive as the lats and/or remedies provided as part of
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted
Exemption: If the declared item does not applicable exemptions.	contain RoHS restricted substances per t	he definition above except for defined Rol	IS exemptions, then select the corresponding	response in the R	oHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	3.35	mg	Supplier	Silicon (Si)	7440-21-3		3.35	mg
Die Attach	0.308	mg	Supplier	Silver (Ag)	7440-22-4		0.231	mg
			Supplier	Phenolic Resin-2	54208-63-8		0.077	mg
Lead Frame	337.967	mg	Supplier	Silver (Ag)	7440-22-4		1.69	mg
			Supplier	Zinc (Zn)	7440-66-6		0.406	mg
			Supplier	Iron (Fe)	7439-89-6		7.77	mg
			Supplier	Copper (Cu)	7440-50-8		328	mg
			Supplier	Phosphorus (P)	7723-14-0		0.101	mg
Mold Compound-Black	711.0	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		142.2	mg
			Supplier	Carbon Black (C)	1333-86-4		7.11	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		561.69	mg
Plating	24.7	mg	Supplier	Tin (Sn)	7440-31-5		24.7	mg
Wire Bond - Au	0.397	mg	Supplier	Gold (Au)	7440-57-5		0.397	mg