	ASSOCIATION CONNECTING	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lo level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
Company name* Company name* Company unique ID Unique ID Authority Response Date* 2023-06-08 Contact Name Title - Contact Title - Contact Phone - Contact* Phone - Contact* Phone - Contact* Email - Contact* Email - Contact* Product-Env-Stewards Outhorized Representative* Title - Representative Title - Representative Phone - Representative* Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards NA Product-Env-Stewards Onsemi.com Nanufacturing Site Weight* UOM Wanufacturing Proccess Information Vanufacturing Proccess Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles Matte Tin (Sn) - annealed COMMENTATION - Seconds 3 Comments	752-21.1					*						ıformatio	on		
Semil	upplier Inform	ation													
Title - Contact Name Product Enviro Compliance Title - Representative* Product Enviro Compliance Title - Representative* Product Enviro Compliance Title - Representative* Product Enviro Compliance NA Product Env-Stewards NA Product Env-Stewards NA Product Env-Stewards NA Product Env-Stewards NA Naunfacturing Site Weight* UOM NCP1219AD65R2G ANA PWM CONTROLLER 2023-06-08 NCP1219AD65R2G ANA PWM CONTROLLER Producturing Proccess Information Terminal Plating / Grid Array Material Terminal Base Alloy NCP1219AD65R2G ANA PWM CONTROLLER Peak Process Body Temperature Naun Time at Peak Temperature Number of Reflow Cycles And Time at Peak Temperature Number of Reflow Cycles And Temperature Num	Company name* Company unique ID					Unique ID Authority				Response Date*					
Product-Env-Stewards	nsemi											2023-06-08			
Authorized Representative* Product-Env-Stewards Requester Item Number Mfr Item Number Manufacturing Site Meight* Weight* UOM NCPU23-06-08 CNW Manufacturing Site Meight* Monufacturing Site Mo	Contact Name			Title - Conta	ct		1	Phone - Contac	et*			Email - Con	tact*		
Product Envi-Stewards Requester Item Number Mfr Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM NCP1219AD65R2G ANA PWM CONTROLLER 2023-06-08 CNW 80.48 mg I Manufacturing Process Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Matte Tin (Sn) - annealed CU Alloy I 260 C 30 Seconds 3 Comments	Product-Env-Stewa	rds		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com			
Requester Item Number	uthorized Represei	ntative*	Title - Representative			I	Phone - Representative*				Email - Representative*				
NCP1219AD65R2G ANA PWM CONTROLLER 2023-06-08 CNW 80.48 mg I	Product-Env-Stewards Product J				oduct Enviro Compliance			NA				Product-Env-Stewards@onsemi.com			
Manufacturing Proccess Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles Matte Tin (Sn) - annealed CU Alloy 1 260 C 30 seconds 3	Requester	r Item Number	Mfr Item	Number	Mfr Item Name			Effective Date	Version	N	Anufacturing Site	Wei	ght*	UOM	Unit Type
Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles Matte Tin (Sn) - annealed CU Alloy 1 260 C 30 seconds 3			NCP1219	AD65R2G	ANA PWM CONT	ROLLER		2023-06-08		C	NW	80.4	3	mg	Each
Matte Tin (Sn) - annealed CU Alloy 1 260 C 30 seconds 3 comments				amainal Daga	Allow	CTD 020 MCI	I. Dotino	Dool: Droo	aga Dady Ta		May Time at Peak	Townsoroture	Numb	or of Potlan, Cya	lac.
omments					Alloy J-	S I D-020 MSI	L Kating		ess Body 16	_				er of Reflow Cyc	ies
	•	n (Sn) - annealed	C	U Alloy	1			200		<u> </u> C	30	seconds	3		
VELT - MAXIMUM UME AL DEAK TEMDEFALUFE QUEINS SOIGEFINS IS 10-50 SECONOS		ima at naak tampanatura	dunina sala	dowing is 10.2	10 accords										
or more information regarding material composition please refer to page 3															

RoHS Material Composition Declaration			Declaration Type *	Detail	ed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		ium (Cr6+), Polybrominated Biphenyls (PB)	erial for Cadmium and quantity limit of 0.1% b B), Polybrominated Diphenyl Ethers (PBDE), a		
cadmium, hexavalentchromium, polybromin contains a RoHS restricted substance inexce encompass all such components. Supplier cet as of the date that Supplier completes this Company acknowledges that Supplier may hindependently verified information provided certification in this paragraph. If the Compan	nated biphenyls and/or polybrominated diphess of an applicable quantity limit, please indriffes that it gathered the information it provom. Supplier acknowledges that Company wave relied on informationprovided by others of the supplier agrees that, at a minimusy and the Supplier enter into a written agree yesource of the Supplier's liability and the C	enyl ethers (each a "RoHS restricted substan licate below which, if any, RoHS exemption vides in this form using appropriate methods vill rely on this certification in determining the s in completing this form, and that Supplier um, itssuppliers have provided certifications ement with respect to the identified part, the tompany's remedies for issues that arise rega	s of the European Union member states) of the ce") in excess of the applicable quantity limit is you believe may apply. If the part is an assemb to ensure its accuracy and that such informatio e compliance of its products with European Ur may not have independently verified such infor regarding their contributions to the part, and the erms and conditions of that agreement, including information the Supplier provides in this	dentified above. If a ally with lower level in is true and correct at it in member state la mation. However, in ose certifications are ag any warranty righ	homogeneous material within the part components, the declaration shall to the best of its knowledge and belief, was that implement the RoHS Directive. In situations where Supplier has not the at least as comprehensive as the lats and/or remedies provided as part of
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted
Exemption: If the declared item does not applicable exemptions.	contain RoHS restricted substances per t	he definition above except for defined Rol	IS exemptions, then select the corresponding	response in the R	oHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	2.52	mg	Supplier	Silicon (Si)	7440-21-3		2.52	mg
Die Attach	0.43	mg		Epoxy resin	proprietary data		0.043	mg
			Supplier	Ethylene dimethacrylate	97-90-5		0.0215	mg
			Supplier	Silver (Ag)	7440-22-4		0.344	mg
			Supplier	Formaldehyde Polymer	9003-36-5		0.0215	mg
Lead Frame	27.82	mg	Supplier	Silver (Ag)	7440-22-4		0.1669	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0334	mg
			Supplier	Iron (Fe)	7439-89-6		0.6538	mg
			Supplier	Copper (Cu)	7440-50-8		26.9576	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0083	mg
Mold Compound-Black	48.72	mg		Epoxy resin	proprietary data		2.436	mg
			Supplier	Phenolic Resin	Proprietary Data		2.436	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.9744	mg
			Supplier	Carbon Black (C)	1333-86-4		0.2436	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		42.63	mg
Plating	0.94	mg	Supplier	Tin (Sn)	7440-31-5		0.94	mg
Wire Bond - Cu	0.05	mg	Supplier	Copper (Cu)	7440-50-8		0.05	mg