

LINEAR TECHNOLOGY MATERIALS DECLARATION

ltc1562cg-2#trpbf

(Engineering Calculation)

SSOP

(printed on: 2020-07-11 21:40:06)

TOTAL MASS (g) : 0.156943

| COMPONENT MATERIAL | VENDOR/ INDUSTRY NAMES | CONSTITUENT NAME | CAS NUMBER | CONSTITUENT MASS (g) | CONSTITUENT (PPM) OF MATERIAL | CONSTITUENT (PPM) OF TOTAL PKG. | | |
|--------------------------------|----------------------------------|--------------------------------|------------|----------------------|-------------------------------|---------------------------------|----------------|----------------------|
| Active Device | Linear Technology | Silicon (Si) | 7440-21-3 | 0.009844 | 1000000 | 62723.5546875 | | |
| Die Coat | Dow Corning | Silicone | 69430-27-9 | 0.000000 | 0 | 0 | | |
| Lead Frame | Cu | Copper (Cu) | 7440-50-8 | 0.058880 | 975000 | 375168.875 | | |
| | | Iron (Fe) | 7439-89-6 | 0.001449 | 24000 | 9232.671875 | | |
| | | Phosphorus (P) | 7723-14-0 | 0.000018 | 300 | 114.691581726 | | |
| | | Zinc (Zn) | 7440-66-6 | 0.000042 | 700 | 267.613677979 | | |
| | | Nickel (Ni) | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Silicon (Si) | 7440-21-3 | 0.000000 | 0 | 0 | | |
| | | Magnesium (Mg) | 7439-95-4 | 0.000000 | 0 | 0 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| Lead Frame Total: | | | | 0.060389 | 1000000 | 384783.875 | | |
| Plating | PMI | Exter. Plating Pb | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Exter. Plating Sn | 7440-31-5 | 0.002831 | 1000000 | 18036.0976562 | | |
| | | External Plating Total: | | | | 0.002831 | 1000000 | 18036.0976562 |
| | | Inter. Plating Ni | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Inter. Plating Ag | 7440-22-4 | 0.000483 | 1000000 | 3077.55737305 | | |
| Internal Plating Total: | | | | 0.000483 | 1000000 | 3077.55737305 | | |
| Die Attach | ELECTRICALLY CONDUCTIVE ADHESIVE | Silver (Ag) | 7440-22-4 | 0.002151 | 750000 | 13705.6435547 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| | | Lead (Pb) | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.000000 | 0 | 0 | | |
| | | Indium (In) | 7440-74-6 | 0.000000 | 0 | 0 | | |
| | | Metal Oxide | | 0.000000 | 0 | 0 | | |
| | | Antimony (Sb) | 7440-36-0 | 0.000000 | 0 | 0 | | |
| | | Resin (EP) | | 0.000717 | 250000 | 4568.54785156 | | |
| Die Attach Total: | | | | 0.002868 | 1000000 | 18274.1914062 | | |
| Encapsulation | MULTI-AROMATIC RESIN Br/Sb FREE | Resin (EP) | | 0.008259 | 103000 | 52624.3203125 | | |
| | | Bromine (Br) | 40039-93-8 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.071761 | 895000 | 457243.4375 | | |
| | | Antimony Trioxide (Sb2O3) | 1309-64-4 | 0.000000 | 0 | 0 | | |
| | | Metal Hydroxide | | 0.000000 | 0 | 0 | | |
| | | Carbon Black (C) | 1333-86-4 | 0.000160 | 2000 | 1019.48065186 | | |
| | | Encapsulation Total: | | | | 0.080180 | 1000000 | 510887.21875 |
| Bond Wire Estimated | AFW/TANAKA/ Kn | Gold (Au) | 7440-57-5 | 0.000348 | 1000000 | 2217.37060547 | | |
| | | | | | TOTAL MASS (g) : | 0.156943 | | |